



NEW



Big Display Battery operated pH/Temp.Monitor 8605

- Large display with smart backlight
- Name card compact size for all locations
- Accurate pH and temperature reading
- Low battery indicator.
- °C/°F unit switchable.
- Power by 4pcs AA batteries.
- Multi points calibration.
- One touch only for calibration.



SENSOR PROTECTION BOTTLE TO EXTEND STORAGE LIFE TIME

Wall mount hook to fix monitor and pH probe to water tank



Wall mount hanger & nylon screw x 2

Various types of pH probes



Low ionic
86P4

Glass
86P6

Sharp
86P7

Surface
86P1



Aquaculture

Ordering Code

- VZ8605AZ, 8605 pH/Temp. Monitor
- VZ8605PNL, 8605 pH probe
- VZ86P2AZ, general use pH probe
- VZ86P4AZ, low ionic use pH probe
- VZ86P6AZ, full glass pH probe
- VZ86P7AZ, sharp tip pH probe
- VZ86P1AZ, flat surface pH probe

*Available for EB project

Model	8605
pH range	0.00~14.00
pH accuracy	+/-0.1
pH resolution	0.01
Temp. range	-5.0~60.0°C
Temp. accuracy	+/-0.5°C
Temp. resolution	0.1
ATC	ATC
LCD size	26(H)x44(W)mm
Operating temp.	0~50°C
Operating RH%	Humidity<80%
Storage temp.	-10~50°C
Storage RH%	Humidity < 90%
Sensor life time	>3 months (with good maintenance)
Dimension	90(L)x63(W)x31(H)mm
Weight	130g
Battery	AA x 4pcs
Backlight	Green Backlight
Standard Package	Meter/pH probe (8605 pH probe)/Battery/Manual /Paper box

